

Battery Charger

BC-1015



MAIN FEATURES

- **4 Independent Charging Channels**
Charge 1-4 pcs AA/AAA Ni-MH rechargeable batteries
- **6-Level Charging Protection**
ΔV Cut Off
Safety Timer Control Protection
Reverse Polarity Protection
Over-current Protection
Short circuit Protection
Defective and No-rechargeable battery detection
- **LED Charging Indicators**

SPECIFICATIONS

Input: 100-240V ~ 50/60Hz 10W
Output: AA: 4 × (1.4V $\overline{\text{---}}$ 0.3A)
AAA: 4 × (1.4V $\overline{\text{---}}$ 0.15A)

BC-1092M



MAIN FEATURES

- **6 Independent Charging Channels**
Charge 1-4 pcs AA/AAA or 1-2 pcs 9V Ni-MH rechargeable batteries
- **6-Level Charging Protection**
ΔV Cut Off
Safety Timer Control Protection
Reverse Polarity Protection
Over-current Protection
Short circuit Protection
Defective and No-rechargeable battery detection
- **LED Charging Indicators**

SPECIFICATIONS

Input: 100-240V ~ 50/60Hz 10W
Output: AA: 4 × (1.4V $\overline{\text{---}}$ 0.3A)
AAA: 4 × (1.4V $\overline{\text{---}}$ 0.15A)
9V: 2 × (9V $\overline{\text{---}}$ 0.03A)

BC-1057M



MAIN FEATURES

- **4 Independent Charging Channels**
Charge 1-4 pcs AA/AAA Ni-MH rechargeable batteries
- **6-Level Charging Protection**
ΔV Cut Off
Safety Timer Control Protection
Reverse Polarity Protection
Over-current Protection
Short circuit Protection
Defective and No-rechargeable battery detection
- **LED Charging Indicators**

SPECIFICATIONS

Input: 5V $\overline{\text{---}}$ 1.5A
Output: AA: 4 × (1.4V $\overline{\text{---}}$ 0.5A)
AAA: 4 × (1.4V $\overline{\text{---}}$ 0.2A)

Accessories: 1*50CM USB-A to C Cable

LBC-323



MAIN FEATURES

- **2 Independent Charging Channels**
Charge 1-2pcs 9V Ni-MH/Li-ion batteries
- **5-Level Charging Protection**
Safety timer control protection
Reverse polarity protection
Over-current protection
Short circuit protection
Defective and no-rechargeable battery detection
- **LED Charging Indicators**

SPECIFICATIONS

Input: 5V $\overline{\text{---}}$ 1.0A
Output: 9V Ni-MH: 1 x (9.5V $\overline{\text{---}}$ 0.08A)
2 x (9.5V $\overline{\text{---}}$ 0.04A)
9V Li-ion: 1 x (7.4V $\overline{\text{---}}$ 0.26A)
2 x (7.4V $\overline{\text{---}}$ 0.13A)

Accessories: 1*50CM USB-A to C Cable

Camelion®

Camelion Battery Co., Ltd.

705, Cyber Times Tower A, Tian'an Cyber Park,
Shenzhen, Guangdong, China
Tel: +86 755 8361 8088
Email: info@camelionbattery.com
www.camelionbattery.com

Canton Fair
15 - 19 April, 2024
Booth No.: Hall 1.1J39.40, K09-10